

RS 301 V + CS 320



Article

Item no. Description

193144 RS 301 V + CS 320 400 V/3~ with LC display in CS maxi housing, buttons for lift/forward/back/autoreturn, 3-series buttons and main switch in the cover, 1,000 mm cable and 5-pin CEE plug

Scope of delivery

• RS 301 V + CS 320 400 V/3~ control unit with LC display in CS maxi housing, buttons for lift/forward/back/auto-return, 3-series button and main switch in cover, 1,000 mm cable and 5-pin CEE plug

Features

Features functions gate control

- 4 programmable relay outputs with 44 functions
- · Integrated cycle counter/goal counter
- 2 programmable inputs with 27 functions (gate)
- · Changing the direction of rotation via circuit board push button/display
- Adjustable power limitation for both running directions (only with AWG)
- Rotation direction monitoring and detection (only with AWG)
- Integrated error memory (readout of all error messages indicating frequency and cycle of last occurrence) only with LCD monitor

Features Ramp control functions

- · For controlling a leveller with feed lip
- Control of 2- or 3-valve units
- 8 valve versions for feed lip control



- · Start-up interlock after power failure
- · Rotary field test/phase failure detection
- 1 programmable input with 4 functions (bridge)
- · Control of the gate sealing (Shelter function)
- · Enabling/locking the automatic gate
- · Release/locking by external gate control
- Auto Return

Features end position adjustment

- Via mechanical limit switches (MEC) and/or via absolute encoders (AWG)
- · Setting via circuit board push button or plug-in LCD monitor

Features operation

- · 3 direction keys
- 3-series push button gate control
- · Auto return button
- Pluggable LC display with plain text display
- 3-button navigation/status and diagnostic messages

Features structure and connection

- · Integrated main switch
- Integrated fuses for the hydraulic power unit (standard: 4 A, on request 6.3 A)
- Switchable transformer from 230 V/1~/3~ to 400 V/3~
- Power supply for external devices (RS: 24 V-DC/250 mA; CS: 24 V-DC/500 mA and 230 V-AC/1 A)
- · Short-circuit proof extra-low voltage
- · Connection of indoor and outdoor traffic lights
- Connection of wheel wedge and start-up sensor
- Connection of loading light or signal horn
- Connection for locking the dock leveller
- · Connection for locking the gate system
- · Connection for elements of the safety circuit
- · Connection for closing edge protection (opto, 8.2 k0hm, pressure wave bar or leading light barrier) in CLOSE direction

Features Optional

- Automatic return
- · Control in steel cabinet

Technical data

- · Housing type: CS-Maxi
- Pushbutton in the control cover: Electronic 3-series pushbutton CS Lift Before Back Auto Return
- Function switch in the control cover: Without function switch
- Main switch in the control cover: Main switch 4-pole
- Emergency stop in the control cover: Without emergency stop
- · Power plug: CEE plug 5-poles. red



- Display type: LCD
- Protection class: IP65
- Temperature (min.) [°C]: -10
- Temperature (max.) [°C]: 45
- Temperature (min./max.)[°C]: -10/45
- Operating mode (control): Deadman
- On-site supply: 180-440 V/3~/N/PE/50/60 Hz
- Mains frequency [Hz]: 50/60
- Control voltage [V]: 24 V-DC
- Switching current gate control(max.)[A]: 8
- Switching current ramp control (max.)[A]: 6.3
- Current consumption per valve (max.)[A]: 0.8
- Load capacity power gate control (max.)[kW]: 2.2
- Load capacity Ramp control power (max.) [kW]: 2.2
- Width [mm]: 260
- Height [mm]: 550
- Depth[mm]: 245
- Packing width: 0
- · Packing height: 0
- Packing depth/length: 0
- Packing weight: 4.504
- Freight forwarding articles: No
- GTIN: 4062435001911
- Customs tariff number: 85371091
- Country of origin 1000: Deutschland
- Garantie: -