


# A profile 35.55 TsTLa



## Article

---

Item no.	Description
186951	A profile 35.55 TsTLa Contact bar profile, 35x55 mm, with sealing lip, 30 m roll

## Scope of delivery

---

- Contact strip profile, 30.000 mm

## Use

---

- For various gate or door types. Can only be used in conjunction with a suitable mounting profile

## Technical data

---

- Material: TPE
- Color: Black
- Temperature (min.)[°C]: -10
- Temperature (max.)[°C]: 50
- Temperature (min./max.)[°C]: -10/50
- Temperature (min.)[°F]: 14
- Temperature (max.)[°F]: 122
- Width [mm]: 35
- Height [mm]: 55
- Length [mm]: 30,000

- Weight per meter [kg]: 0.65
- Packing width: 1,000
- Packing height: 300
- Packing depth/length: 1,200
- Packing weight: 36
- Freight forwarding articles: Yes
- Customs tariff number: 39161000
- Country of origin 1000: Deutschland
- Garantie: -

## Accessories

---

Item no.	Description
99590	<b>Aluminum profile 24x8 mm</b> 2 m
177309	<b>Aluminum profile set 24x8 mm</b> 5 m, 10 pieces
115798	<b>Aluminum profile 25x18 mm</b> 2 m
169153	<b>Aluminum profile 25x14 mm</b> 2 m, for fastening in front of the gate
100893	<b>F stop buffer 2</b> Stop buffer, 55 mm high, with T-nut, 2 pieces
186945	<b>A connector 35.55 - 8.2 kOhm</b> Termination plug with 8.2 kOhm resistor
186954	<b>A plug 35.55 - 0.3 m</b> Connector plug with 0.3 m cable

## Predecessors

---

Item no.	Description	Discontinuation
149869	<b>A profile 35.55 TsTLa</b> Contact strip profile 35x55 mm with sealing lip, 25 m	2021-07-01

Technical drawings

