

EM 181



Article

Item no.	Description
90588	EM 181 MS-Bus extension module with connection for light barrier and opto-sensors Opto 100 with system cabling, top hat rail installation, with 0.14 m MS-Bus cable

Scope of delivery

- Extension module
- Connection cable MS bus RJ14, 140 mm

Features

Features

- 1 programmable input for light barriers with system wiring
- 1 programmable input for OPTO 100 opto-sensors with system wiring
- Status and diagnostic messages via LED
- Installation on a top-hat rail

Use

- For Comfort 260 (speed), 270 (speed), 280, 360, 370, 380, 390 (plus) and VTA

Technical data

- Connection type: Pluggable
- Inputs:
 - 1 programmable input for photoelectric sensors with system wiring
 - 1 programmable input for opto-sensors OPTO 100 with system wiring
- Interfaces: MS bus (RJ14 connector)
- Protection class: IP00
- Temperature (min.) [°C]: -20
- Temperature (max.) [°C]: 60
- Temperature (min./max.) [°C]: -20/60
- Temperature (min.) [°F]: -4
- Temperature (max.) [°F]: 140
- Operating voltage [V]: 24 V-DC
- Operating voltage type: Direct current
- Width [mm]: 45
- Height [mm]: 126
- Depth [mm]: 48
- Width (pitch units): 2.5
- Packing width: 189
- Packing height: 60
- Packing depth/length: 249
- Packing weight: 0.286
- Freight forwarding articles: No
- GTIN: 4062434007075
- Customs tariff number: 85371091
- Country of origin 1000: Deutschland
- Garantie: -