

Protect-Opto 602



Article

Item no.	Description
140539	Protect-Opto 602 Leading light barrier, consisting of DUO receiver and transmitter with 1 m cable, IP54, conventional

Scope of delivery

- F photoelectric sensor DUO transmitter with 1,000 mm cable
- F-Light barrier DUO receiver with 1.000 mm cable
- 2 installation brackets
- 2 floor installation plates
- Installation material

Features

Features

- Optical safety device to protect against personal injury and damage to property

Use

- For controllers with connection for OSE optosensors. Currently not compatible with Comfort 390 plus – please use light grid

Technical data

- Connection type: Conventional
- Protection class: IP54
- Temperature (min.) [°C]: -10
- Temperature (max.) [°C]: 55
- Temperature (min./max.) [°C]: -10/55
- Range [m]: 6
- Operating voltage [V]: 4-28 V-DC
- Power consumption [VA/W/kW]: 0.12 W
- Width [mm]: 52
- Height [mm]: 331
- Depth [mm]: 153
- Weight [kg]: 1.9
- Packing width: 203
- Packing height: 68
- Packing depth/length: 389
- Packing weight: 2.153
- Freight forwarding articles: No
- GTIN: 4062434009123
- Customs tariff number: 85389091
- Country of origin 1000: Deutschland
- Garantie: -