

Digital 890



Article

Item no.	Description
122036	Digital 890 4-channel flush-mounted transmitter, unidirectional, 868 MHz bi.linked

Scope of delivery

- Flush mounted transmitter with battery
- Connection cable, 90 mm

Features

Features

- 4 potential-free inputs for connection for e.g. push buttons - wired pushbuttons thus become wireless push buttons
- High security through 128-bit AES-encrypted radio transmission and constantly changing radio code (rolling code method)

Use

- For all Marantec controllers and third-party products (in conjunction with corresponding bi.linked receiver)

Technical data

- Channels: 4

- Antenna: Wire antenna
- Radio frequency: 868 MHz
- Radio technology: bi.linked
- Radio coding: Marantec
- Communication direction: Unidirectional
- Connection type: Conventional
- Inputs:
4 potential-free inputs for push buttons (NO)
- Protection class: IP20
- Color: RAL 7011
- Installationarea: Flush-mounted
- Temperature (min.)[°C]: -20
- Temperature (max.)[°C]: 60
- Temperature (min./max.)[°C]: -20/60
- Temperature (min.)[°F]: -4
- Temperature (max.)[°F]: 140
- battery type: CR2032, 3 V
- Battery count: 1
- Width [mm]: 37
- Height [mm]: 30
- Depth [mm]: 10
- Packing width: 77
- Packing height: 18
- Packing depth/length: 116
- Packing weight: 0.02
- Freight forwarding articles: No
- GTIN: 4062434003718
- Customs tariff number: 85269200
- Country of origin 1000: Deutschland
- Garantie: 2 years