

Digital 994



Article

Item no.	Description
160280	Digital 994 1-channel flush-mounted receiver with 200 memory locations and one potential-loaded relay, 230 V, unidirectional, 868 MHz bi.linked

Scope of delivery

- Flush-mounted receiver

Features

Features

- 1 channel for free assignment
- 1 potential-loaded relay contact for direct switching of an electrical device, e.g. outdoor lamp
- ON/OFF function
- Generous memory for up to 200 keys
- Compact size

Use

- For all Marantec controllers and third-party products

Technical data

- Channels: 1
- Number of memory locations: 200
- Antenna: Integrated
- Radio frequency: 868 MHz
- Radio technology: bi.linked
- Radio coding: Marantec
- Communication direction: Unidirectional
- Connection type: Conventional
- Contact type: 1 NO
- Outputs:
 - 1 potential-free relay contact (N.O.)
- Protection class: IP00
- Color: RAL 7016
- Temperature (min.)[°C]: -20
- Temperature (max.)[°C]: 60
- Temperature (min./max.)[°C]: -20/60
- Temperature (min.)[°F]: -4
- Temperature (max.)[°F]: 140
- Operating voltage [V]: 230 V/1~
- Operating voltage type: Alternating current
- Power consumption [VA/W/kW]: 0.8 W
- Power consumption in standby [VA/W/kW]: 0.25 W
- Contact load (max.):
 - 230 V-AC/10 A/2,300 VA
- Width [mm]: 48
- Height [mm]: 48
- Depth [mm]: 25
- Packing width: 59
- Packing height: 53
- Packing depth/length: 78
- Packing weight: 0.06
- Freight forwarding articles: No
- GTIN: 4062434008690
- Customs tariff number: 85269200
- Country of origin 1000: Deutschland
- Garantie: 2 years