

EM 185 in CS mini housing



Article

Item no.	Description
184081	EM 185 in CS mini housing MS bus extension module with connection for one light grid OSE, in CS mini housing, with 9.5 m MS bus cable

Scope of delivery

- Extension module pre-assembled in CS mini housing
- Connection cable MS-Bus RJ14, 9.500 mm
- Installation material

Features

Features

- One programmable input with OSE signal processing and function logic for OSE light curtain (12/24 V-DC/max. 0.6 W)
- Connection of a 2nd OSE light grid using a 2nd EM module. Both modules can be accommodated in a CS mini housing and operated in series connection to the control
- Status and diagnostic messages via LED
- Installation on a top-hat rail
- Weather resistant housing

Use

- For Comfort 260 (speed), 270 (speed), 280, 360, 370, 380, 390 (plus) and VTA

Technical data

- Connection type: Pluggable
- Inputs:
 - 1 programmable input for light barriers with 2-wire cabling
 - 1 programmable input with OSE signal processing and function logic for OSE light curtains (12/24 V-DC/max. 0.6 W)
- Interfaces: MS bus (RJ14 connector) 2-wire OSE
- Protection class: IP65
- Temperature (min.) [°C]: -20
- Temperature (max.) [°C]: 60
- Temperature (min./max.) [°C]: -20/60
- Temperature (min.) [°F]: -4
- Temperature (max.) [°F]: 140
- Operating voltage [V]: 24 V-DC
- Operating voltage type: Direct current
- Width [mm]: 165
- Height [mm]: 220
- Depth [mm]: 105
- Packing width: 170
- Packing height: 105
- Packing depth/length: 240
- Packing weight: 1.825
- Freight forwarding articles: No
- GTIN: 4062434014622
- Customs tariff number: 85423190
- Country of origin 1000: Deutschland
- Garantie: -