

# Back-up 700



## Article

---

Item no.	Description
87786	<b>Back-up 700</b> Battery backup, 7.2 Ah, in IP20 housing

## Scope of delivery

---

- Battery unit with integrated charge controller
- Connection cable, 1,000 mm
- Wall bracket with mounting hardware

## Features

---

### Features

- Signaling of charging status and errors via LED
- Max. 70 cycles service life within 7 days at an ambient temperature of +20 °C in conjunction with an opener in blueline mode
- Max. 30 cycles period of use within 3 days at an ambient temperature of +20 °C in conjunction with an operator or a control system with power-saving mode

## Use

---

- For Comfort 260 (speed), 270 (speed), 280, 360, 370, 380, 390 (plus), Control x.52 and x.82

## Technical data

---

- Connection type: Pluggable
- Inputs:
  - 1 common entrance and exit for loading and supply
- Outputs:
  - 1 common entrance and exit for loading and supply
- Protection class: IP20
- Temperature (min.)[°C]: -15
- Temperature (max.)[°C]: 45
- Temperature (min./max.)[°C]: -15/45
- Temperature (min.)[°F]: 5
- Temperature (max.)[°F]: 113
- Operating voltage [V]: 24 V-DC
- Operating voltage type: Direct current
- Battery capacity [Ah]: 7.2
- Width [mm]: 230
- Height [mm]: 280
- Depth [mm]: 80
- Packing width: 290
- Packing height: 175
- Packing depth/length: 340
- Packing weight: 5.25
- Freight forwarding articles: No
- GTIN: 4062434007204
- Customs tariff number: 85072080
- Country of origin 1000: Deutschland
- Garantie: -