

Digital 992 IP65



Article

Item no.	Description
116881	Digital 992 IP65 2-channel universal receiver with 100 memory locations per relay, 24 V, IP65, unidirectional, 868 MHz bi.linked

Scope of delivery

- Universal receiver
- Mounting material

Features

Features

- Weather resistant housing
- 2 channels for free assignment
- 2 potential-free relay contacts for switching electrical devices, e.g. impulse input of a gate control system
- IMPULSE or ON/OFF function separately adjustable for each channel
- Generous memory for up to 100 keys per channel
- Connection with conventional wiring for external push buttons for direct switching of each relay

Use

- For all Marantec controllers and third-party products

Technical data

- Number of memory locations: 100
- Antenna: Wire antenna
- Radio frequency: 868 MHz
- Radio technology: bi.linked
- Radio coding: Marantec
- Communication direction: Unidirectional
- Connection type: Conventional
- Contact type: 2 CO
- Inputs:
2 inputs for potential-free push buttons (NO)
- Outputs:
2 potential-free relay contacts (CO)
- Protection class: IP65
- Color: RAL 7011
- Temperature (min.)[°C]: -20
- Temperature (max.)[°C]: 60
- Temperature (min./max.)[°C]: -20/60
- Temperature (min.)[°F]: -4
- Temperature (max.)[°F]: 140
- Operating voltage [V]: 12-24 V-AC 12-24 V-DC
- Operating voltage type: Alternating current or direct current
- Rated current [A]: 0.05
- Contact load (max.):
24 V-AC/1 A/24 VA; 30 V-DC/1 A/30 W
- Width [mm]: 70
- Height [mm]: 113
- Depth [mm]: 35
- Packing width: 87
- Packing height: 72
- Packing depth/length: 125
- Packing weight: 0.163
- Freight forwarding articles: No
- GTIN: 4062434002216
- Customs tariff number: 85269200
- Country of origin 1000: Deutschland
- Garantie: 2 years

Accessories

Item no.	Description
102957	Magnetic foot antenna Magnetic foot antenna with 5 m cable, conventional, 868 MHz
193418	Taster-Anschlusskabel zum Anschluss von Tastern an Universalempfänger Digital 33x.2/34x.2/992