

Special 633 L



Article

Item no.	Description
101182	Special 633 L Through beam photoelectric switch with 20 m range, +/- 90° rotatable, 2-wire, IP65, with 20 m ground cable

Scope of delivery

- Light barrier transmitter
- Light barrier receiver
- 2 housings
- Connecting cable 2x0,8 mm², 20.000 mm
- Installation material

Features

Features

- Horizontal alignment of the light beam by 180°
- Function and contamination signaling by LED
- 2-wire technology: supply, signal and testing via only 2 polarity reversal protected and connectable wires
- Optical safety device to protect against personal injury and damage to property

Use

- For controls with connection for 2-wire light barriers

Technical data

- Connection type: Conventional
- Interfaces: 2-wire
- Protection class: IP65
- Range [m]: 20
- Range (min.) [m]: 6
- Range (max.) [m]: 20
- Operating voltage [V]: 24 V-DC
- Width [mm]: 38
- Height [mm]: 110
- Depth [mm]: 38
- Packing width: 190
- Packing height: 115
- Packing depth/length: 270
- Packing weight: 0.995
- Freight forwarding articles: No
- GTIN: 4062434001103
- Customs tariff number: 85365080
- Garantie: 2 years

Accessories

Item no.	Description
104186	Protective cover set for Special 633 (L/R) made of aluminum, 2 pieces
97559	Special 670 Light barrier expander for connecting 2 pieces of 2-wire light barriers to one input

Technical drawings

