

Special 630



Article

Item no.	Description
88176	Special 630 Through beam photoelectric sensor with 8 m range, 2-wire, IP54, with 2x 10 m cable

Scope of delivery

- Light barrier transmitter
- Light barrier receiver
- 2 connecting cables, 10.000 mm
- 4 cable connectors
- Installation material

Features

Features

- Function and contamination signaling by LED
- 2-wire technology: supply, signal and testing via only 2 polarity reversal protected and connectable wires
- Suitable for installation in the CH-51N and CH-101N pedestals
- Optical safety device to protect against personal injury and damage to property

Use

- For controls with connection for 2-wire light barriers

Technical data

- Connection type: Conventional
- Interfaces: 2-wire
- Protection class: IP54
- Range [m]: 8
- Range (min.)[m]: 1
- Range (max.)[m]: 8
- Operating voltage [V]: 24 V-DC
- Width [mm]: 27
- Height [mm]: 64.5
- Depth [mm]: 19
- Packing width: 130
- Packing height: 35
- Packing depth/length: 200
- Packing weight: 0.292
- Freight forwarding articles: No
- GTIN: 4062434000403
- Customs tariff number: 85365080
- Country of origin 1000: Deutschland
- Garantie: 2 years

Accessories

Item no.	Description
97559	Special 670 Light barrier expander for connecting 2 pieces of 2-wire light barriers to one input
88175	Installation bracket set for Special 630 light barrier
88175	Installation bracket set for Special 630 light barrier
178438	CH-51N Poles for LS22 or Special 630 photoelectric barriers, 0.5 m height, set of 2
198148	CH-51N Säule für Lichtschranken LS22 oder Special 630, 0,5 m Höhe
178439	CH-101N Columns for light barriers LS22 or Special 630, 1.0 m height, set of 2
97559	Special 670 Light barrier expander for connecting 2 pieces of 2-wire light barriers to one input

Technical drawings

