

EM 173 in a CS small housing



Article

Item no.	Description
198701	EM 173 in a CS small housing EM 173 Expansion Module with 4 Inputs/Outputs for Home Automation in a CS small housing, including a 3-meter MS-Bus cable

Scope of delivery

- Extension module pre-assembled in CS mini housing
- Connection cable MS bus 4-pin/MS bus RJ14, 3,000 mm
- Installation material

Features

Features

- 3 potential-free inputs for controlling open, close, and intermediate positions (ventilation position)
- 1 potential-free input for interrupting the holding circuit (e.g., while on vacation)
- 3 potential-free relay contacts for reporting the end position (OPEN), CLOSE, and intermediate (ventilation) positions
- 1 potential-free relay contact for reporting an interrupted 2-wire photoelectric barrier (e.g., to detect a problem during remote closing)
- Status and diagnostic messages via LED
- Installation on a top-hat rail
- Weather resistant housing

Use

- For Comfort 260 (speed), 270 (speed), 280, 360, 370, and 380

Technical data

- Connection type: Pluggable
- Contact type: 4 CO
- Inputs:
4 potential-free inputs for push buttons (NO)
- Outputs:
4 potential-free relay contacts (CO)
- Interfaces: MS bus (RJ14 connector) MS bus (4-pin connector)
- Protection class: IP65
- Temperature (min.) [°C]: -20
- Temperature (max.) [°C]: 60
- Temperature (min./max.) [°C]: -20/60
- Temperature (min.) [°F]: -4
- Temperature (max.) [°F]: 140
- Operating voltage [V]: 24 V-DC
- Operating voltage type: Direct current
- Contact load (max.):
230 V/6 A
- Width [mm]: 165
- Height [mm]: 220
- Depth [mm]: 105
- Packing width: 210
- Packing height: 100
- Packing depth/length: 350
- Packing weight: 0.9
- Freight forwarding articles: No
- GTIN: 4062434026519
- Customs tariff number: 85371091
- Country of origin 1000: Deutschland

Predecessors

Item no.	Description	Discontinuation
191759	Electrical accessories with four inputs for OPEN/STOP/CLOSE/light and three relays for OPEN/CLOSE/light, in IP65 housing	2026-01-20