

Draw-in protection



Article

Item no.	Description
96150	Draw-in protection with 10 m range, 24 V-DC, OSE, IP68, with 10.5/10.5 cable pre-mounted

Scope of delivery

- Transmitter with pull in safety device, 10,500 mm connection cable
- Receiver with pull in safety device , 10,500 mm connection cable
- 2 installation brackets

Features

Features

- Optical safety device to protect against personal injury and damage to property

Use

- For controls with connection for OSE pull-in safety devices

Technical data

- Connection type: Conventional

- Interfaces: OSE
- Protection class: IP68
- Temperature (min.)[°C]: -10
- Temperature (max.)[°C]: 55
- Temperature (min./max.)[°C]: -10/55
- Temperature (min.)[°F]: 14
- Temperature (max.)[°F]: 131
- Range [m]: 10
- Range (min.)[m]: 0
- Range (max.)[m]: 10
- Operating voltage [V]: 24 V-DC
- Rated current [A]: 0.06
- Width [mm]: 73
- Height [mm]: 40
- Depth [mm]: 20
- Cable length [m]: 10.5
- Weight [kg]: 0.7
- Packing width: 225
- Packing height: 50
- Packing depth/length: 248
- Packing weight: 0.705
- Freight forwarding articles: No
- GTIN: 4062435001515
- Customs tariff number: 84799070
- Country of origin 1000: Deutschland
- Garantie: -