

EM 184



Article

Item no.	Description
105733	EM 184 MS bus extension module with connection for 2 pull-in safety devices OSE/PNP/relay, DIN rail including, with 0.2 m MS bus cable

Scope of delivery

- Extension module
- Connecting cable, 200 mm

Features

Features

- 2 programmable inputs with testing for pull-in fuses with OSE/PNP/relay connection (24-30 V-DC/max. 0.2 A)
- Automatic detection of the connected system
- Activation in OPEN or CLOSE direction selectable
- Supply voltage of the pull-in safety fuse selectable device (12/24 V-DC)
- Status and diagnostic messages via LED
- Installation on a top-hat rail

Use

- For Comfort 260 (speed), 270 (speed), 280, 360, 370, 380, 390 (plus), VTA, CS 265 and CS 320

Technical data

- Connection type: Pluggable
- Inputs:
2 programmable inputs for pull-in fuses with OSE/PNP/relay connection (24-30 V-DC/max. 0.2 A)
- Interfaces: MS bus (RJ14 connector) MS bus (4-pin connector) OSE PNP
- Protection class: IP00
- Temperature (min.) [°C]: -20
- Temperature (max.) [°C]: 60
- Temperature (min./max.) [°C]: -20/60
- Temperature (min.) [°F]: -4
- Temperature (max.) [°F]: 140
- Operating voltage [V]: 24 V-DC
- Operating voltage type: Direct current
- Width [mm]: 45
- Height [mm]: 126
- Depth [mm]: 48
- Width (pitch units): 2.5
- Packing width: 160
- Packing height: 65
- Packing depth/length: 239
- Packing weight: 0.245
- Freight forwarding articles: No
- GTIN: 4062434015421
- Customs tariff number: 84799015
- Country of origin 1000: Deutschland
- Garantie: -