

Throughbeam photoelectric sensor 24-240 V-AC/DC



Article

Item no.	Description
96372	Throughbeam photoelectric sensor 24-240 V-AC/DC with 10 m range, 24-240 V-AC/DC, 4-wire, IP66, without cable, with installation brackets

Scope of delivery

- Light barrier transmitter
- Light barrier receiver
- 2 installation brackets

Features

Features

- Optical safety device to protect against personal injury and damage to property

Use

- For controls with connection for 4-wire light barriers

Technical data

- Connection type: Conventional
- Outputs:
 - 1 potential-free relay contact (CO)
- Protection class: IP66
- Temperature (min.)[°C]: -25
- Temperature (max.)[°C]: 55
- Temperature (min./max.)[°C]: -25/55
- Temperature (min.)[°F]: -13
- Temperature (max.)[°F]: 131
- Range [m]: 50
- Range (min.)[m]: 0
- Range (max.)[m]: 50
- Operating voltage [V]: 24-240 V-AC/-DC
- Power consumption [VA/W/kW]: 7 VA
- Contact load (max.):
 - 240 V-AC/30 V-DC/3 A
- Width [mm]: 23.5
- Height [mm]: 74.5
- Depth [mm]: 63
- Weight [kg]: 0.32
- Packing width: 83
- Packing height: 85
- Packing depth/length: 91
- Packing weight: 0.369
- Freight forwarding articles: No
- GTIN: 4062435001508
- Customs tariff number: 84799070
- Country of origin 1000: Volksrepublik China
- Garantie: -

Technical drawings

