

1-channel radio signal transmission system



Article

Item no.	Description
164276	1-channel radio signal transmission system 868 MHz, consisting of: 2-channel receiver IP55 and 1-channel transmitter for one safety contact (NC) or one 8.2 kOhm contact strip, battery operated, IP67

Scope of delivery

- 1-channel receiver
- 1-channel transmitter with 2 batteries

Features

1-channel receiver

Features

- Radio receiver-transmitter system for maximum safety and quick installation
- Bidirectional 868 MHz transmission of up to 7 transmitters per receiver and with up to 10 m range
- 2 different frequencies to avoid interferences
- Test input for standard-compliant safeguarding

Transmitter

Features

- Radio receiver-transmitter system for maximum safety and quick installation
- Bidirectional 868 MHz transmission of up to 7 transmitters per receiver and with up to 10 m range

- Connection option for an 8.2 kOhm contact strip or a safety circuit (NC)
- Up to 2 years battery life (replacement recommended during annual maintenance)
- Acoustic signal in case of low battery

Use

Transmitter

- For receiver for radio transmission system 868 MHz

Technical data

1-channel receiver

- Channels: 1
- Radio frequency: 868 MHz
- Connection type: Conventional
- Number of contacts: 1
- Contact type: 1 NC
- Inputs:
 - 1 Test input
- Outputs:
 - 1 potential-free relay contact (NC)
- Safety category: 2
- Protection class: IP55
- Temperature (min.) [°C]: -20
- Temperature (max.) [°C]: 55
- Temperature (min./max.) [°C]: -20/55
- Temperature (min.) [°F]: -4
- Temperature (max.) [°F]: 131
- Range [m]: 10
- Operating voltage [V]: 12 V-AC 12 V-DC 24 V-AC 24 V-DC
- Power consumption [VA/W/kW]: 1.2 W
- Contact load (max.):
 - 24 V/0.5 A
- Width [mm]: 127
- Height [mm]: 81
- Depth [mm]: 46
- Weight [kg]: 0.13

Transmitter

- Channels: 1
- Radio frequency: 868 MHz
- Connection type: Conventional
- Number of contacts: 1
- Contact type: 1 NC
- Inputs:
1 input for a safety circuit (NC) or an 8.2 kOhm contact strip
- Interfaces: 8.2 kOhm
- Safety category: 2
- Protection class: IP67
- Temperature (min.)[°C]: -20
- Temperature (max.)[°C]: 55
- Temperature (min./max.)[°C]: -20/55
- Temperature (min.)[°F]: -4
- Temperature (max.)[°F]: 131
- Range [m]: 10
- Rated current [A]: 0.017
- battery type: CR2032, 3 V
- Battery count: 2
- Width [mm]: 183
- Height [mm]: 51
- Depth [mm]: 36
- Weight [kg]: 0.13
- Packing width: 63
- Packing height: 55
- Packing depth/length: 195
- Packing weight: 0.168
- Freight forwarding articles: No
- GTIN: 4062435001133
- Customs tariff number: 85269200
- Country of origin 1000: Spanien
- Garantie: -