

# Through-beam photoelectric sensor 12-24 V-AC/-DC



## Article

---

Item no.	Description
99165	Through-beam photoelectric sensor 12-24 V-AC/-DC with 10 m range, 12-24 V-AC/-DC, 4-wire, IP65, with pre-mounted 12 m/3 m cable

## Scope of delivery

---

- Light barrier transmitter with 12.000 mm connection cable
- Light barrier receiver with 3.000 mm connection cable

## Features

---

### Features

- Optical safety device to protect against personal injury and damage to property

## Use

---

- For controls with connection for 4-wire light barriers

## Technical data

---

- Connection type: Conventional
- Outputs:  
1 potential-free relay contact (CO)
- Interfaces: 4-wire
- Protection class: IP65
- Temperature (min.)[°C]: -20
- Temperature (max.)[°C]: 60
- Temperature (min./max.)[°C]: -20/60
- Temperature (min.)[°F]: -4
- Temperature (max.)[°F]: 140
- Range [m]: 10
- Range (min.)[m]: 0
- Range (max.)[m]: 10
- Operating voltage [V]: 12-24 V-AC 12-24 V-DC
- Rated current [A]: 0.08
- Width [mm]: 40
- Height [mm]: 144
- Depth [mm]: 60
- Weight [kg]: 0.93
- Packing width: 0
- Packing height: 0
- Packing depth/length: 0
- Packing weight: 0.88
- Freight forwarding articles: No
- GTIN: 4062434006740
- Customs tariff number: 84799070
- Country of origin 1000: Deutschland
- Garantie: -

## Accessories

Item no.	Description
120448	<b>Accessories bag rail mounting light barrier</b> Installation bracket for throughbeam photoelectric sensor 12-24 V-AC/DC, set of 2

Technical drawings

