

# Barrier arm support



## Article

---

Item no.	Description
183826	<b>Barrier arm support</b> in RAL 7047, 0,89-1,05 m high, with 24 V-DC magnetic lock

## Scope of delivery

---

- Height adjustable barrier arm support with impact damper
- Lock 730 electromagnet, installation plate, anchor plate, 10,000 mm connection cable 4x0.75 mm<sup>2</sup> and installation material

## Use

---

### Barrier arm support

- For round barrier arm ASTL4(J)/5(J)/6(J)/8

### Lock 730

- For boom arm ASTL4(J)/5(J)/6(J)/8. Only in conjunction with forked support post with receptacle for magnetic locking

## Technical data

---

### Barrier arm support

- Material: Steel (galvanized)

- Color: RAL 7047
- Installationarea: Foundation
- Width [mm]: 150
- Height (min.)[mm]: 890
- Height (max.)[mm]: 1,050
- Height (min.-max.)[mm]: 890-1050
- Depth [mm]: 150
- Packing width: 193
- Packing height: 170
- Packing depth/length: 1,134
- Packing weight: 5.347
- Freight forwarding articles: No
- GTIN: 4062434019771
- Customs tariff number: 86080000
- Country of origin 1000: Italien
- Garantie: -

## Lock 730

- Connection type: Conventional
- Protection class: IP65
- Holding force (max.)[N]: 1,400
- Operating voltage [V]: 24 V-DC
- Rated current [A]: 0.35
- Power consumption [VA/W/kW]: 8.5 W
- Packing width: 0
- Packing height: 0
- Packing depth/length: 0
- Packing weight: 1.4
- Freight forwarding articles: No
- GTIN: 4062434014691
- Customs tariff number: 85059021
- Country of origin 1000: Deutschland
- Garantie: -