

Comfort ST5024E



Article

Item no.

Description

178377

 $\textbf{Comfort ST5024E} \ \texttt{Operator for swing gates up to 5.0 m: 24 V DC motor, 1,400 N, 2.7 cm/s, 122°, with a superior of the state of$

encoder

Scope of delivery

- Motor unit, pre-wired, 500 mm (2x1.5 and 3x0.5 mm² required)
- · Gate and angle bracket for welding

Features

Comfort ST5024E

Features

- Current-dependent obstacle detection no active closing edge protection necessary
- Built-in encoder for maximum precision
- Mechanical end stop in end position CLOSED necessary
- Mechanical stop in OPEN for end position control
- Driver on spindle with double bearings for maximum smooth running
- · Robust metal gearbox
- Very quiet mechanism
- All mechanical parts protected against weather influences
- Sturdy and UV-resistant plastic housing
- Gate and pillar angle for easy motor installation



· Lockable unlocking device

Technical data

Comfort ST5024E

- · Encoder: Yes
- Continuous sound pressure level (max.) [dB(A)]: 70
- Connection type: Conventional
- · Protection class: IP44
- Width gate wing (max.)[m]: 5
- Height gate wing (max.)[m]: 2
- Weight of gate leaf (max.) [kg]: 600
- Gradient (max.) [%]: 0
- Temperature (min.)[°C]: -20
- Temperature (max.) [°C]: 55
- Temperature (min./max.)[°C]: -20/55
- Temperature (min.)[°F]: -4°F
- Temperature (max.) [°F]: 131°F
- Push and pull force (max.)[N]: 1,400
- Operating mode (duty cycle): S2 8 min
- Motor power [kW]: 0.12
- Running speed (max.) [cm/s]: 2.7
- Opening angle (max.)[°]: 122
- Operating voltage [V]: 24 V-DC
- Operating voltage type: Direct current
- Motor voltage [V]: 24 V-DC
- Rated current [A]: 5
- Width [mm]: 108
- Height [mm]: 110
- Depth[mm]: 995
- Depth (min.) [mm]: 995
- Depth (max.) [mm]: 995
- Movement stroke (max.) [mm]: 490
- Weight [kg]: 9.5
- Garantie: 5 years

Accessories

Item no. Description

178402 **STPOAVS** Pillar bracket



ltem no.	Description
178403	STANAV Gate bracket
178461	CBX20224H Control for up to 2 24 V-DC operators for swing gates, with integrated radio receiver 868 MHz bi.linked and 230 V-AC transformer in housing
178466	EXRB Angle extension for opening to the outside
178404	FC-PS Mechanical end stop in direction CLOSE
178391	ELS-C 12 V-DC electric lock for pillar locking from a wing span of 2.5 m
178403	STANAV Gate bracket

178402 STPOAVS Pillar bracket
178466 EXRB Angle extension for opening to the outside
178404 FC-PS Mechanical end stop in direction CLOSE

178391 ELS-C 12 V-DC electric lock for pillar locking from a wing span of 2.5 m



Technical drawings

Comfort ST5024E

