

MILAN



Article

Item no.	Description
148763	MILAN Active infrared presence sensor, 2.5 to 6.0 m installation height, IP65 with 10 m cable

Scope of delivery

- Presence sensor
- Connection cable, 10.000 mm

Features

Features

- Contactless protection of gate, persons or objects by presence detection in the entrance of the gate
- Customizable detection field and minimum size of objects to be detected

Use

- For all Marantec controls and third-party products

Technical data

- Connection type: Conventional

- Contact type: 2 CO
- Outputs:
2 potential-free relay contacts (CO)
- Sensoren: Active infrared
- Wave length [nm]: 875
- Protection class: IP65
- Color: Black
- Installation height (min.) [m]: 2.5
- Installation height (max.) [m]: 6
- Installation height (min./max.) [m]: 2.5/6
- Temperature (min.) [°C]: -30
- Temperature (max.) [°C]: 60
- Temperature (min./max.) [°C]: -30/60
- Temperature (min.) [°F]: -22
- Temperature (max.) [°F]: 140
- Active infrared detection field (max. WxL) [m]: 4x4
- Operating voltage [V]: 12-24 V-AC 12-24 V-DC
- Operating voltage type: Alternating current or direct current
- Power consumption [VA/W/kW]: 3.5 W
- Contact load (max.):
42 VA/30 W
- Width [mm]: 127
- Height [mm]: 102
- Depth [mm]: 96
- Packing width: 0
- Packing height: 0
- Packing depth/length: 0
- Packing weight: 0.892
- Freight forwarding articles: No
- GTIN: 4062434013724
- Customs tariff number: 90318080
- Country of origin 1000: Volksrepublik China
- Garantie: -

Accessories

Item no.	Description
148657	Remote control Infrared remote control for setting radar motion detectors and laser scanners
148764	Spotfinder Detector for infrared light curtains, presence sensor

Technical drawings



