

Special 632



Article

Item no.

Description

95519

Special 632 Through beam photoelectric sensor for installation in Parc 300 and columns, 8 m range,

2-wire, IP54, with 20 m cable

Scope of delivery

- Light barrier transmitter
- · Light barrier receiver
- 2 holders for 32 mm holes
- 1 installation bracket for installation in the Parc 300
- 1 Special 633 housing for alternative surface mounting
- Connecting cable, 20.000 mm
- 4 cable connectors
- · Installation material

Features

Features

- Function and contamination signaling by LED
- 2-wire technology: supply, signal and testing via only 2 polarity reversal protected and connectable wires
- Optical safety device to protect against personal injury and damage to property



Use

• For Parc 300 and columns with 32 mm borehole diameter

Technical data

• Connection type: Conventional

Interfaces: 2-wireProtection class: IP54

• Range [m]: 8

Range (min.)[m]: 1

• Range (max.)[m]: 8

• Operating voltage [V]: 24 V-DC

Width[mm]: 27Height[mm]: 64Depth[mm]: 19Packing width: 279

Packing height: 183

• Packing depth/length: 310

• Packing weight: 2.184

• Freight forwarding articles: No

• GTIN: 4062434015520

Customs tariff number: 85365019Country of origin 1000: Deutschland

• Garantie: 2 years

Accessories

Item no. Description

97559 Special 670 Light barrier expander for connecting 2 pieces of 2-wire light barriers to one input



Technical drawings

