

Reflex light barrier 24 V-AC/DC



Article

Item no.	Description
90747	Reflex light barrier 24 V-AC/DC with 12 m range, 4-wire, IP65, without cable

Scope of delivery

- Light barrier transmitter/receiver
- Reflector 80 mm

Features

Features

- The reflector saves the laying of a cable from the control to the opposite side of the gate
- Optical safety device to protect against personal injury and damage to property

Use

- For controls with connection for 4-wire light barriers

Technical data

- Connection type: Conventional

- Inputs:
1 Test input
- Outputs:
1 potential-free relay contact (NC)
- Interfaces: 4-wire
- Protection class: IP65
- Temperature (min.)[°C]: -25
- Temperature (max.)[°C]: 60
- Temperature (min./max.)[°C]: -25/60
- Temperature (min.)[°F]: -13
- Temperature (max.)[°F]: 140
- Range [m]: 12
- Range (min.)[m]: 0.5
- Range (max.)[m]: 12
- Operating voltage [V]: 10-40 V-AC/-DC
- Rated current [A]: 0.03
- Contact load (max.):
0.5 A/48 V-DC, 0.6 A/50 V-AC
- Width [mm]: 45
- Height [mm]: 87
- Depth [mm]: 40
- Weight [kg]: 0.15
- Packing width: 98
- Packing height: 50
- Packing depth/length: 149
- Packing weight: 0.159
- Freight forwarding articles: No
- GTIN: 4062435001522
- Customs tariff number: 85365019
- Country of origin 1000: Deutschland
- Garantie: -

Technical drawings

