

# Power supply 24 V-DC/2.5 A in CS mini housing



## Article

| Item no. | Description                                                                                                                |
|----------|----------------------------------------------------------------------------------------------------------------------------|
| 184828   | <b>Power supply 24 V-DC/2.5 A in CS mini housing</b> 2 outputs, in CS mini housing, IP65, with 1.5 m cable and Schuko plug |

## Scope of delivery

- Power supply unit pre-assembled in CS mini housing and pre-wired with 1,500 mm connection cable

## Features

### Features

- Wide universal input voltage range
- Adjustable output voltage
- Connections protected against accidental contact
- Weather resistant housing

## Use

- For all Marantec controllers and third-party products

## Technical data

---

- Connection type: Conventional
- Inputs:  
1
- Outputs:  
2
- Protection class: IP65
- Temperature (min.)[°C]: -30
- Temperature (max.)[°C]: 70
- Temperature (min./max.)[°C]: -30/70
- Temperature (min.)[°F]: -22
- Temperature (max.)[°F]: 158
- Output power [kW]: 0.06
- Input voltage [V]: 85-264 V/1~
- Output voltage [V]: 24 V-DC
- Nominal frequency [Hz]: 50/60
- Output current [A]: 2.5
- Power consumption [VA/W/kW]: 66.7 W
- Width [mm]: 165
- Height [mm]: 220
- Depth [mm]: 105
- Packing width: 0
- Packing height: 0
- Packing depth/length: 0
- Packing weight: 1.02
- Freight forwarding articles: No
- GTIN: 4062434014561
- Customs tariff number: 85044060
- Country of origin 1000: Deutschland
- Garantie: -