

Emergency power buffer 230 V/2000 VA



Article

Item no.	Description
188601	Emergency power buffer 230 V/2000 VA Emergency power buffer 230 V/2,000 VA in housing

Scope of delivery

- Emergency power buffer with integrated charge controller

Features

Features

- In the event of a mains voltage failure, the emergency power buffer system automatically switches on and supplies the door control unit and operator. As soon as the mains voltage is available again, the door control unit and operator are supplied again via the mains and the accumulators of the emergency power buffer are charged
- Simple commissioning according to the plug & play principle: battery buffer and door control are connected directly via Schuko plug. No additional control cable required between battery and door control
- When the accumulator is fully charged, a door cycle can be guaranteed for a period of one hour

Use

- For STA 1 operators with CS 320 FU controls

Technical data

- Protection class: IP44
- Temperature (min.)[°C]: 0
- Temperature (max.)[°C]: 40
- Temperature (min./max.)[°C]: 0/40
- Output power [kW]: 1.4
- Input voltage [V]: 220-240 V-AC
- Output voltage [V]: 230 V/1~
- Mains frequency [Hz]: 50/60
- Battery capacity [Ah]: 18
- Width [mm]: 600
- Height [mm]: 400
- Depth [mm]: 210
- Weight [kg]: 25
- Packing width: 0
- Packing height: 0
- Packing depth/length: 0
- Packing weight: 28
- Freight forwarding articles: No
- GTIN: 4062434014387
- Customs tariff number: 85078000
- Country of origin 1000: Deutschland
- Garantie: -