

MILAN



Article

ltem no.

Description

148763

MILAN Active infrared presence sensor, 2.5 to 6.0 m installation height, IP65 with 10 m cable

Scope of delivery

- Presence sensor
- Connection cable, 10.000 mm

Features

Features

- Contactless protection of gate, persons or objects by presence detection in the entrance of the gate
- Customizable detection field and minimum size of objects to be detected

Use

• For all Marantec controls and third-party products

Technical data

• Connection type: Conventional



- Contact type: 2 CO
- Outputs:

2 potential-free relay contacts (CO)

Sensoren: Active infraredWave length [nm]: 875

• Protection class: IP65

· Color: Black

• Installation height (min.)[m]: 2.5

• Installation height (max.)[m]: 6

• Installation height (min./max.)[m]: 2.5/6

• Temperature (min.) [°C]: -30

• Temperature (max.) [°C]: 60

• Temperature (min./max.)[°C]: -30/60

• Temperature (min.) [°F]: -22

• Temperature (max.) [°F]: 140

• Active infrared detection field (max. WxL)[m]: 4x4

Operating voltage [V]: 12-24 V-AC 12-24 V-DC

· Operating voltage type: Alternating current or direct current

• Power consumption [VA/W/kW]: 3.5 W

 Contact load (max.): 42 VA/30 W

• Width [mm]: 127

Height [mm]: 102

• Depth[mm]: 96

· Packing width: 0

· Packing height: 0

• Packing depth/length: 0

• Packing weight: 0.892

• Freight forwarding articles: No

• GTIN: 4062434013724

• Customs tariff number: 90318080

• Country of origin 1000: Volksrepublik China

• Garantie: -

Accessories

Item no.Description148657Remote control Infrared remote control for setting radar motion detectors and laser scanners148764Spotfinder Detector for infrared light curtains, presence sensor



Technical drawings





