marantec
engineered for you

Barrier arm support

Article

Item no.	Description
183826	**Barrier arm support** in RAL 7047, 0,89-1,05 m high, with 24 V-DC magnetic lock

Scope of delivery

- Height adjustabe barrier arm support with impact damper
- Lock 730 electromagnet, installation plate, anchor plate, 10,000 mm connection cable 4x0.75 mm^2 and installation material

Use

Barrier arm support

- For round barrier arm ASTL4(J)/5(J)/6(J)/8

Lock 730

- For boom arm ASTL4(J)/5(J)/6(J)/8. Only in conjunction with forked support post with receptacle for magnetic locking

Technical data

Barrier arm support

- Installation type: Screw on

- Material: Steel (galvanized)
- Color: RAL 7047
- Installationarea: Foundation
- Width [mm]: 150
- Height (min.) [mm]: 890
- Height (max.) [mm]: 1,050
- Height (min.-max.) [mm]: 890-1050
- Depth [mm]: 150
- Packing width: 193
- Packing height: 170
- Packing depth/length: 1,134
- Packing weight: 5.347
- Freight forwarding articles: No
- GTIN: 4062434019771
- Customs tariff number: 86080000
- Country of origin 1000: Italien
- Garantie: -

Lock 730

- Connection type: Conventional
- Protection class: IP65
- Holding force (max.) [N]: 1,400
- Operating voltage [V]: 24 V-DC
- Rated current [A]: 0.35
- Power consumption [VA/W/kW]: 8.5 W
- Packing width: 0
- Packing height: 0
- Packing depth/length: 0
- Packing weight: 1.4
- Freight forwarding articles: No
- GTIN: 4062434014691
- Customs tariff number: 85059021
- Country of origin 1000: Deutschland
- Garantie: -