Through-beam photoelectric sensor 12-24 V-AC/-DC



Article

Item no.	Description
99165	**Through-beam photoelectric sensor 12-24 V-AC/-DC** with 10 m range, 12-24 V-AC/-DC, 4-wire, IP65, with pre-mounted 12 m/3 m cable

Scope of delivery

- Light barrier transmitter with 12.000 mm connection cable
- Light barrier receiver with 3,000 mm connection cable

Features

Features

- Optical safety device to protect against personal injury and damage to property

Use

- For controls with connection for 4-wire light barriers

Technical data

- Connection type: Conventional
- Outputs:
  1 potential-free relay contact (CO)
- Interfaces: 4-wire
- Protection class: IP65
- Temperature (min.) [°C]: -20
- Temperature (max.) [°C]: 60
- Temperature (min./max.) [°C]: -20/60
- Temperature (min.) [°F]: -4
- Temperature (max.) [°F]: 140
- Range [m]: 10
- Range (min.) [m]: 0
- Range (max.) [m]: 10
- Operating voltage [V]: 12-24 V-AC 12-24 V-DC
- Rated current [A]: 0.08
- Width [mm]: 40
- Height [mm]: 144
- Depth [mm]: 60
- Weight [kg]: 0.93
- Packing width: 250
- Packing height: 50
- Packing depth/length: 330
- Packing weight: 0.88
- Freight forwarding articles: No
- GTIN: 4062434006740
- Customs tariff number: 84799070
- Country of origin 1000: Deutschland
- Garantie: -

Accessories

Item no.	Description
120448	**Accessories bag rail mounting light barrier** Installation bracket for throughbeam photoelectric sensor 12-24 V-AC/DC, set of 2

Technical drawings

