

Special 632 L



Article

Item no.	Description
103359	Special 632 L Through beam photoelectric sensor for installation in Parc 300 and columns, 20 m range, 2-wire, IP54, with 20 m cable

Scope of delivery

- Light barrier transmitter
- Light barrier receiver
- 2 holders for 32 mm holes
- 1 mounting bracket for installation in the Parc 300
- 1 Special 633 housing for alternative surface mounting
- 2 connecting cable, 10.000 mm
- 4 cable connectors
- Installation material

Features

Features

- Function and contamination signaling by LED
- 2-wire technology: supply, signal and testing via only 2 polarity reversal protected and connectable wires
- Optical safety device to protect against personal injury and damage to property

Use

- For Parc 300 and columns with 32 mm borehole diameter

Technical data

- Connection type: Conventional
- Interfaces: 2-wire
- Protection class: IP54
- Range [m]: 20
- Range (min.) [m]: 6
- Range (max.) [m]: 20
- Operating voltage [V]: 24 V-DC
- Width [mm]: 27
- Height [mm]: 64
- Depth [mm]: 19
- Packing width: 270
- Packing height: 175
- Packing depth/length: 300
- Packing weight: 1.17
- Freight forwarding articles: No
- GTIN: 4062434015438
- Customs tariff number: 85269200
- Country of origin 1000: Deutschland
- Garantie: 2 years

Accessories

Item no.	Description
97559	Special 670 Light barrier expander for connecting 2 pieces of 2-wire light barriers to one input

Technical drawings

