


F receiver pluggable



Article

Item no.	Description
119200	F receiver pluggable 0.4 m cable, pluggable, OSE

Scope of delivery

- F photoelectric sensor receiver with 400 mm cable and connector (Molex)

Use

- For controls with connection for OSE opto-sensors. For door leaf junction boxes with connection for pluggable safety elements

Technical data

- Connection type: Pluggable
- Interfaces: OSE
- Protection class: IP68
- Temperature (min.) [°C]: -20
- Temperature (max.) [°C]: 75
- Temperature (min./max.) [°C]: -20/75
- Range [m]: 10
- Operating voltage [V]: 4-28 V-DC
- Diameter [mm]: 11

- Length [mm]: 37
- Cable length [m]: 0.4
- Weight [kg]: 0.03
- Packing width: 0
- Packing height: 0
- Packing depth/length: 0
- Packing weight: 0.032
- Freight forwarding articles: No
- GTIN: 4062435001256
- Customs tariff number: 85365019
- Country of origin 1000: Deutschland
- Garantie: -

Accessories

Item no.	Description
166375	F spacer sleeve set 11/14 mm for opto-sensors, 2 pieces
79834	F spacer sleeve set 11/22 mm for opto-sensors, 2 pieces
165235	F spacer sleeve 11/22 mm with steel insert for opto-sensors