


A profile 25.45 TTLa



Article

Item no.	Description
186949	A profile 25.45 TTLa Contact bar profile, 25x45 mm, with sealing lip, 30 m roll

Scope of delivery

- Contact strip profile, 30.000 mm

Use

- For various gate or door types. Can only be used in conjunction with a suitable mounting profile

Technical data

- Material: TPE
- Color: Black
- Temperature (min.)[°C]: -10
- Temperature (max.)[°C]: 50
- Temperature (min./max.)[°C]: -10/50
- Temperature (min.)[°F]: 14
- Temperature (max.)[°F]: 122
- Width [mm]: 25
- Height [mm]: 45
- Length [mm]: 30,000

- Weight per meter [kg]: 0.5
- Packing width: 1,000
- Packing height: 300
- Packing depth/length: 1,200
- Packing weight: 29
- Freight forwarding articles: Yes
- Customs tariff number: 40082900
- Country of origin 1000: Deutschland
- Garantie: -

Accessories

Item no.	Description
99590	Aluminum profile 24x8 mm 2 m
177309	Aluminum profile set 24x8 mm 5 m, 10 pieces
115798	Aluminum profile 25x18 mm 2 m
169153	Aluminum profile 25x14 mm 2 m, for fastening in front of the gate
122954	F stop buffer 3 Stop buffer, 46 mm high, with T-nut, 2 pieces
186944	A connector 25.45 - 8.2 kOhm Termination plug with 8.2 kOhm resistor
186953	A plug 25.45 - 0.3 m Connector plug with 0.3 m cable

Predecessors

Item no.	Description	Discontinuation
149910	A profile 25.45 TTLa Contact strip profile 25x45 mm with sealing lip, 25 m	2021-07-01

Technical drawings

