marantec
engineered for you

US 1-2T/1



Article

Item no.	Description
184191	**US 1-2T/1** Key switch for flush installation, 2-sided momentary contact, metal housing, IP54, 3 keys

Scope of delivery

- Key switch with profile half cylinder (30/10 mm - 0°) and 3 keys
- Recessed box for 60 mm drill holes

Features

Features

- 2 interchangeable contacts with push-button function (key left/right)
- Integrated flush-mounting box for flush-mounting installation in drilled holes with a diameter of 60 mm
- Large front panel to cover tearouts or plaster when installing in masonry
- Burglar resistant due to robust metal housing and access to the inside with the help of the key

Use

- For all Marantec controls and third-party products

Technical data

- Connection type: Conventional
- Number of contacts: 2
- Contact type: 2 NO
- Switch function: 2-sided scanning
- Protection class: IP54
- Material: Aluminum die casting Aluminum
- Installationarea: Flush-mounted
- Width [mm]: 90
- Height [mm]: 100
- Depth [mm]: 55.5
- Packing width: 100
- Packing height: 80
- Packing depth/length: 117
- Packing weight: 0.3435
- Freight forwarding articles: No
- GTIN: 4062434013380
- Customs tariff number: 85365080
- Country of origin 1000: Deutschland
- Garantie: -