

# 2-channel radio transmission system pluggable



# **Article**

Item no. Description

**2-channel radio transmission system pluggable** 868 MHz, consisting of: 2-channel plug-in receiver for CS 320 and 2-channel transmitter for 2 signals (NC/NO/OSE/8.2 kOhm), battery operated, IP67

# Scope of delivery

- · 2-channel receiver circuit board
- 2-channel transmitter with 2 batteries

# **Features**

# 2-channel plug-in receiver

#### **Features**

- Radio receiver-transmitter system for maximum safety and quick installation
- Bidirectional 868 MHz transmission of up to 7 transmitters per receiver and with up to 10 m range
- 2 different frequencies to avoid interferences
- Can be plugged directly into the CS 320 controller
- · Test function for standard-compliant safeguarding



# 2 channel transmitter

#### **Features**

- Radio receiver-transmitter system for maximum safety and quick installation
- Bidirectional 868 MHz transmission of up to 7 transmitters per receiver and with up to 10 m range
- Connection options: OSE + 8.2 kOhm; OSE + NC/NO; 2x 8.2 kOhm; 8.2 kOhm + NC/NO
- Up to 2 years battery life (replacement recommended during annual maintenance)
- · Acoustic signal in case of low battery

### Use

# 2 channel transmitter

• For receiver for radio transmission system 868 MHz

# Technical data

# 2-channel plug-in receiver

• Channels: 2

• Radio frequency: 868 MHz

· Connection type: Pluggable

· Safety category: 2

• Protection class: IP00

• Temperature (min.) [°C]: -20

• Temperature (max.)[°C]: 55

• Temperature (min./max.) [°C]: -20/55

• Temperature (min.)[°F]: -4

• Temperature (max.) [°F]: 131

• Range [m]: 10

• Operating voltage [V]: 5 V-DC

• Width [mm]: 35

• Height [mm]: 40

• Depth [mm]: 12

# 2 channel transmitter

• Channels: 2

· Radio frequency: 868 MHz

· Connection type: Conventional

• Number of contacts: 2

• Inputs:



- 1 input for a safety circuit (NC/NO) or a closing edge fuse (OSE/8.2 kOhm) 1 input for a safety circuit (NC/NO) or a closing edge fuse (8.2 kOhm)
- Interfaces: OSE 8.2 kOhm
- · Safety category: 2
- Protection class: IP67
- Temperature (min.)[°C]: -20
- Temperature (max.)[°C]: 55
- Temperature (min./max.)[°C]: -20/55
- Temperature (min.) [°F]: -4
- Temperature (max.)[°F]: 131
- Range [m]: 10
- Rated current [A]: 0.017
- battery type: AA, 3.6 V (lithium)
- Battery count: 2
- Width [mm]: 183
- Height [mm]: 51
- Depth[mm]: 36
- Weight [kg]: 0.13
- Packing width: 68
- Packing height: 55
- Packing depth/length: 197
- Packing weight: 0.201
- Freight forwarding articles: No
- GTIN: 4062435001126
- Customs tariff number: 85269200
- Country of origin 1000: Spanien
- Garantie: -