

Transmitter



Article

Item no.

Description

123738

Transmitter for radio transmission from one safety contact (NC) or one 8.2 kOhm contact strip, battery operated, IP67, 868 MHz

Scope of delivery

• Transmitter with 2 batteries

Features

Features

- Radio receiver-transmitter system for maximum safety and quick installation
- Bidirectional 868 MHz transmission of up to 7 transmitters per receiver and with up to 10 m range
- Connection option for an 8.2 kOhm contact strip or a safety circuit (NC)
- Up to 2 years battery life (replacement recommended during annual maintenance)
- Acoustic signal in case of low battery

Use

• For receiver for radio transmission system 868 MHz



Technical data

• Channels: 1

• Radio frequency: 868 MHz

• Connection type: Conventional

• Number of contacts: 1

· Contact type: 1 NC

• Inputs:

1 input for a safety circuit (NC) or an 8.2 kOhm contact strip

• Interfaces: 8.2 k0hm

• Safety category: 2

• Protection class: IP67

• Temperature (min.) [°C]: -20

• Temperature (max.) [°C]: 55

• Temperature (min./max.)[°C]: -20/55

• Temperature (min.) [°F]: -4

• Temperature (max.) [°F]: 131

• Range [m]: 10

• Rated current [A]: 0.017

• battery type: CR2032, 3 V

• Battery count: 2

• Width [mm]: 183

• Height [mm]: 51

• Depth[mm]: 36

• Weight [kg]: 0.13

• Packing width: 0

• Packing height: 0

• Packing depth/length: 0

• Packing weight: 0.168

• Freight forwarding articles: No

• GTIN: 4062435001133

• Customs tariff number: 85269200

• Country of origin 1000: Spanien

• Garantie: -