

Command 802



Article

Item no.	Description
81076	Command 802 RFID transponder system with 30 memory locations, consisting of: Evaluation unit with reader module, IP54, 2 m cable and 3 transponder code cards

Scope of delivery

- Reading module with integrated evaluation unit and 2,000 mm connection cable
- 3 transponder code cards
- Voltage converter from 24 V DC to 12 V DC
- Mounting hardware

Features

Features

- Contactless operation by holding a transponder in front of it
- Memory for up to 30 transponders
- IMPULSE or ON/OFF function adjustable
- Targeted programming and deletion of individual transponders

Use

- For all Marantec controllers and third-party products

Technical data

- Number of memory locations: 30
- Radio frequency: 125 kHz
- Connection type: Conventional
- Number of contacts: 1
- Contact type: 1 CO
- Inputs:
 - 1 potential-free push button input (NO)
- Outputs:
 - 1 potential-free relay contact (CO)
- Interfaces: EM4102
- Protection class: IP54
- Temperature (min.) [°C]: -10
- Temperature (max.) [°C]: 60
- Temperature (min./max.) [°C]: -10/60
- Temperature (min.) [°F]: 14
- Temperature (max.) [°F]: 140
- Range [m]: 0.05
- Operating voltage [V]: 12 V-AC 12 V-DC
- Operating voltage type: Direct current
- Rated current [A]: 0.06
- Power consumption [VA/W/kW]: 0.8 W
- Contact load (max.):
 - 2,5 A
- Width [mm]: 39
- Height [mm]: 75
- Depth [mm]: 15
- Packing width: 133
- Packing height: 65
- Packing depth/length: 394
- Packing weight: 0.557
- Freight forwarding articles: No
- GTIN: 4062434000304
- Customs tariff number: 84719000
- Country of origin 1000: Südafrika
- Garantie: 2 years

Accessories

Item no.	Description
8009748	RFID transponder code card
8009749	RFID Transponder Keychain