

EM 172 in CS mini housing



Article

Item no.	Description
121722	EM 172 in CS mini housing MS-Bus expansion module with 4 inputs and 4 outputs in CS mini housing, including 3 m MS-Bus cable

Scope of delivery

- Extension module pre-assembled in CS mini housing
- Connection cable MS bus 4-pin/MS bus RJ14, 3,000 mm
- Installation material

Features

Features

- 4 programmable inputs
- 4 programmable potential-free relay contacts
- Status and diagnostic messages via LED
- Installation on a top-hat rail
- Weather resistant housing

Use

- For CS 265 and CS 320

Technical data

- Connection type: Pluggable
- Contact type: 4 CO
- Inputs:
4 programmable potential-free inputs for pushbuttons (NO)
- Outputs:
4 programmable potential-free relay contacts (CO)
- Interfaces: MS bus (RJ14 connector) MS bus (4-pin connector)
- Protection class: IP65
- Temperature (min.) [°C]: -20
- Temperature (max.) [°C]: 60
- Temperature (min./max.) [°C]: -20/60
- Temperature (min.) [°F]: -4
- Temperature (max.) [°F]: 140
- Operating voltage [V]: 24 V-DC
- Operating voltage type: Direct current
- Contact load (max.):
230 V/6 A
- Width [mm]: 165
- Height [mm]: 220
- Depth [mm]: 105
- Packing width: 0
- Packing height: 0
- Packing depth/length: 0
- Packing weight: 1.8
- Freight forwarding articles: No
- GTIN: 4062434009413
- Customs tariff number: 85371091
- Country of origin 1000: Deutschland
- Garantie: -