

PowLess ceiling pull switch



Article

Item no.	Description
148745	PowLess ceiling pull switch 1-channel ceiling pull switch, piezo function (battery-free), IP65, unidirectional, 868 MHz PowLess

Scope of delivery

- Ceiling pull switch

Features

Features

- Battery-independent supply via an electrodynamic energy generator that converts the mechanical energy into electrical energy when the switch is actuated

Use

- For CS 320 (in conjunction with corresponding PowLess receiver)

Technical data

- Antenna: Integrated
- Radio frequency: 2.4 GHz

- Radio technology: PowLess
- Radio coding: Schneider
- Communication direction: Unidirectional
- Protection class: IP66
- Temperature (min.)[°C]: -25
- Temperature (max.)[°C]: 70
- Temperature (min./max.)[°C]: -25/70
- Temperature (min.)[°F]: -13
- Temperature (max.)[°F]: 158
- battery type: Without
- Width [mm]: 56
- Height [mm]: 144
- Depth [mm]: 38
- Rope weight (max.)[kg]: 0.15
- Packing width: 70
- Packing height: 68
- Packing depth/length: 169
- Packing weight: 0.182
- Freight forwarding articles: No
- Customs tariff number: 85269200
- Country of origin 1000: Deutschland
- Garantie: -

Technical drawings



