

Digital 361



Article

Item no.	Description
65654	Digital 361 1-channel flush-mounted receiver with one potential relay, 230 V, unidirectional, 868 MHz Multi-Bit

Scope of delivery

- Flush-mounted receiver

Features

Features

- 1 channel for free assignment
- 1 potential-loaded relay contact for direct switching of an electrical device, e.g. outdoor lamp
- ON/OFF function
- Compact size

Use

- For all Marantec controllers and third-party products

Technical data

- Channels: 1
- Number of memory locations: 1
- Antenna: Wire antenna
- Radio frequency: 868 MHz
- Radio technology: Multi-Bit
- Radio coding: Marantec
- Communication direction: Unidirectional
- Connection type: Conventional
- Contact type: 1 NO
- Outputs:
 - 1 potential-loaded relay contact (NO)
- Protection class: IP40
- Color: RAL 7011
- Temperature (min.)[°C]: -20
- Temperature (max.)[°C]: 60
- Temperature (min./max.)[°C]: -20/60
- Temperature (min.)[°F]: -4
- Temperature (max.)[°F]: 140
- Operating voltage [V]: 230 V/1~
- Operating voltage type: Alternating current
- Rated current [A]: 0.03
- Power consumption [VA/W/kW]: 6.9 W
- Contact load (max.):
 - 230 V/6 A/1,380 VA
- Width [mm]: 45
- Height [mm]: 45
- Depth [mm]: 25
- Packing width: 58
- Packing height: 53
- Packing depth/length: 79
- Packing weight: 0.073
- Freight forwarding articles: No
- GTIN: 4011805049169
- Customs tariff number: 85269200
- Country of origin 1000: Deutschland
- Garantie: 2 years