

# Back-up 400



#### **Article**

ltem no.

Description

87787

Back-up 400 Battery backup, 4.5 Ah, in IP65 housing

## Scope of delivery

- Battery unit with integrated charge controller
- Connection cable, 1,000 mm

#### **Features**

#### **Features**

- · Weather resistant housing
- · Signaling of charging status and errors via LED
- Max. 10 cycles period of use within 24 hours at an ambient temperature of +20 °C in conjunction with an operator or a control system with power-saving mode

#### Use

• For Comfort 260 (speed), 270 (speed), 280, 360, 370, 380, 390 (plus), Control x.52 and x.82

### Technical data



- · Connection type: Pluggable
- Inputs:
  - 1 common entrance and exit for loading and supply
- Outputs:
  - 1 common entrance and exit for loading and supply
- Protection class: IP65
- Temperature (min.) [°C]: -15
- Temperature (max.) [°C]: 45
- Temperature (min./max.)[°C]: -15/45
- Temperature (min.) [°F]: 5
- Temperature (max.) [°F]: 113
- Operating voltage [V]: 24 V-DC
- Operating voltage type: Direct current
- Battery capacity [Ah]: 4.5
- Width [mm]: 120
- Height [mm]: 240
- Depth [mm]: 100
- Packing width: 290
- Packing height: 175
- Packing depth/length: 340
- Packing weight: 5.25
- Freight forwarding articles: No
- GTIN: 4062434007198
- Customs tariff number: 85072080
- Country of origin 1000: Deutschland
- Garantie: -