

EM 171 in a CS small housing



Article

Item no.	Description
198731	EM 171 in a CS small housing MS-Bus expansion module with 2 programmable relays in a CS small housing, including a 3-meter MS-Bus cable

Scope of delivery

- Extension module pre-assembled in CS mini housing
- Connection cable MS bus 4-pin/MS bus RJ14, 3,000 mm
- Installation material

Features

Features

- 2 programmable potential-free relay outputs (changeover contacts)
- Status and diagnostic messages via LED
- Installation on a top-hat rail
- Weather resistant housing

Use

- For Comfort 260 (speed), 270 (speed), 280, 360, 370, 380, 390 (plus), Control x.52, x.82 and VTA

Technical data

- Connection type: Pluggable
- Contact type: 2 CO
- Outputs:
2 programmable potential-free relay outputs (CO)
- Interfaces: MS bus (RJ14 connector) MS bus (4-pin connector)
- Protection class: IP65
- Temperature (min.) [°C]: -20
- Temperature (max.) [°C]: 60
- Temperature (min./max.) [°C]: -20/60
- Temperature (min.) [°F]: -4
- Temperature (max.) [°F]: 140
- Operating voltage [V]: 24 V-DC
- Operating voltage type: Direct current
- Contact load (max.):
230 V/6 A
- Width [mm]: 165
- Height [mm]: 220
- Depth [mm]: 105
- Packing width: 210
- Packing height: 105
- Packing depth/length: 335
- Packing weight: 0.82
- Freight forwarding articles: No
- GTIN: 4062434026915
- Customs tariff number: 85371091
- Country of origin 1000: Deutschland

Predecessors

Item no.	Description	Discontinuation
85236	Relay retrofit kit Extension circuit board with 3 relays for OPEN/CLOSE/Light, system wiring, in IP65 housing	2025-11-20