

LZR-FLATSCAN SW



Article

Item no.	Description
178521	LZR-FLATSCAN SW Laser motion detector and safety sensor for hinged doors and folding gates, 4.0 m diagonal detection field, with 10 m cable, set of 2 (left and right)

Scope of delivery

- Fuse sensor

Features

Features

- Contactless protection of gate, persons or objects by presence detection

Use

- For all Marantec controls and third-party products

Technical data

- Connection type: Conventional
- Inputs:
 - 1 Test input

- Outputs:
2 potential-free relay contacts
- Sensoren: Laser
- Wave length [nm]: 905
- Protection class: IP54
- Color: Black
- Temperature (min.) [°C]: -30
- Temperature (max.) [°C]: 60
- Temperature (min./max.) [°C]: -30/60
- Temperature (min.) [°F]: -22
- Temperature (max.) [°F]: 140
- Detection field laser (WxL max.) [m]: 4x4
- Operating voltage [V]: 12-24 V-DC
- Operating voltage type: Direct current
- Power consumption [VA/W/kW]: 2 W
- Contact load (max.):
42 V-AC/DC/0.1 A
- Width [mm]: 142
- Height [mm]: 85
- Depth [mm]: 33
- Packing width: 0
- Packing height: 0
- Packing depth/length: 0
- Packing weight: 0.5
- Freight forwarding articles: No
- GTIN: 4062434019825
- Customs tariff number: 85261000
- Garantie: -

Accessories

Item no.	Description
179025	Protective cover Protective cover for LZR flatscan, left version
179026	Protective cover Protective cover for LZR flatscan, right version
184827	Power supply 24 V-DC/2.5 A 2 outputs, top hat rail installation
184828	Power supply 24 V-DC/2.5 A in CS mini housing 2 outputs, in CS mini housing, IP65, with 1.5 m cable and Schuko plug
148657	Remote control Infrared remote control for setting radar motion detectors and laser scanners